

QuickTrace[®] M-8000

CVAF Mercury Analyzer



The QuickTrace® M-8000 Cold Vapor Atomic Fluorescence mercury analyzer (CVAFA) is ideal for ultra-trace to sub-mg/L mercury quantitation. It provides the performance and productivity needed by today's laboratories to meet the tightening regulatory demands, while exceptional stability and user defined QC sequencing allow for long periods of unattended operation.

The QuickTrace® M-8000 mercury analyzer easily achieves the ultra-trace mercury detection limit of < 0.05 ng/L demanded by customers employing EPA method 1631. The QuickTrace® M-8000 is also versatile enough to analyze samples > 400 µg/L without dilution.



Key Features of the QuickTrace® M-8000

The triple mode, no enrichment, single or double gold amalgamation QuickTrace® M-8000 CVAF system from Teledyne Leeman Labs is the system of choice for labs wanting to meet the most stringent reporting limits for academic research or enhanced waste discharge limits demanded by the "Clean Water Act".

- Non-foaming Gas Liquid Separator (GLS) with overflow prevention system
- Automatic end of run and inactivity standby routines
- ≤ 0.05 ng/L instrument detection limits
- Advanced contamination control, over range and smart rinse features
- Intuitive gas controls eliminating air infusion into the system during sample probe movements during mode 2 and 3 analysis
- EPA 1631 and EPA 245.7 compliant (gold amalgamation modes)
- "Smart Rack" technology
- 12-roller 4-channel peristaltic pump
- Sample volume 0.5 mL to > 50 mL
- Unlimited QC sample positions





Performance

The QuickTrace® M-8000 mercury analyzer easily achieves the ultra-trace mercury detection limit of < 0.05 ng/L demanded by customers employing EPA method 1631. The QuickTrace® M-8000 is also versatile enough to analyze samples > 400 µg/L without dilution.

Depending on your laboratory's requirements, the QuickTrace® M-8000 mercury analyzer supports three modes of operation:

Mode 1: Cold Vapor Atomic Fluorescence (CVAF)

Mode 2: Cold Vapor Atomic Fluorescence Single Gold Trap Amalgamation (CVAF-SGTA)



Mode 3: Cold Vapor Atomic Fluorescence Double Gold Trap Amalgamation (CVAF-DGTA)

The QuickTrace® M-8000 modes can be changed without hardware or tubing configuration changes.

Excellent short and long term stability are found in our QuickTrace® M-8000 CVAF analyzer. Less than 0.02 ng/L instrument detection limits are typical for the QuickTrace® M-8000 gold trap modes utilizing less than 25 mL of sample. Non-gold trap instrument detection limits of less than 0.1 ng/L utilizing less than 10 mL of sample can be achieved.

- Ultra-trace detection limits (< 0.05 ng/L IDL)
- Linearity greater than 4 orders of magnitude
- Dynamic range < 0.05 ng/L to > 400 µg/L
- In Mode 1 by response comparison to a 100 ng/L standard, the system exhibits < 0.01% memory effect of a 1 mg/L standard immediately following the ingestion of a 1 part per million (mg/L) sample.
- In Mode 1 without employing our smart rinse technology the system is ready to accurately measure a sample within four minutes following the ingestion of a 1 mg/L sample
- Mode 2 & 3 - Short term precision (%RSD @ 95% Confidence) ≤ 2.5% @ 5 ng/L, n=5

For ultra-trace analysis we recommend our autosampler enclosure to protect the samples from determinate errors such as dust particles. The enclosure will also protect your investment from the harsh acid gases normally present in and around digested samples.



Gold Trap Smart Rinse

We also employ cost saving features during the gold trap desorption such as shutting down the flowing rinse and slowing the SnCl₂ flow. These innovative features can save the laboratory thousands of dollars per year by reducing reagent and waste costs.

Applications*

EPA Methods: 245.7, 1631 and SW 846-7474. EU Methods: Din ISO 16772 and ISO 17852.

*For a full list of applicable methods contact your sales specialist.




QuickTrace®

Teledyne Leeman Labs has designed the multi-tasking QuickTrace® software package to be easy to learn, yet provide valuable features and flexibility while continuously adding customer requested features, truly making the software designed by the customer for the customer.

Features of the QuickTrace® Software platform:

- Microsoft® Windows® 10
- User defined method threshold for over range response values and smart rinse technology
- User defined smart rack technology within a given method. This technology allows the autosampler the use of racks varying in size from 90, 60, 40, 24 or 21 tube position racks for samples, standards or quality control
- True Multi-tasking
- Simultaneously run analyses, develop methods, and print reports
- EPA 245.7 and 1631 quality control compliant
- User defined blank acceptance criteria for EPA 245.7 and 1631
- Customizable quality control features
- User defined one or two point baseline offset correction
- Integrate via peak height or peak area
- Scheduled consumable maintenance tracking
- Data files are efficiently exported to a network via the Ethernet port for convenient linking to a Laboratory Information Management System (LIMS)
- Data files can be emailed to, and opened by, a Teledyne Leeman Labs representative on a PC
- Online help for immediate software support
- Automatic detection limit calculation - determine EPA defined IDL/MDL
- Real time exportable data-tracking log
- Individualized reports - customize printouts by selecting from several parameters
- Master worksheets - ready-to-run worksheets allow quick operation for new users





Freedom of Choice

Teledyne Leeman Labs provides customers the freedom to choose an autosampler for their mercury analyzer that will meet their laboratories sample load requirements. The ASX-280 and ASX-560 autosamplers are available for any QuickTrace™ Mercury Analyzers. Manual sampling is also available with the option to add autosamplers as sample demand increases.

ASX Standard Autosampler Specifications		
	ASX-280	ASX-560
Tray	10 Standards, 2 Sample Racks	10 Standards, 4 Sample Racks
Capacity	180 samples	360 samples
Dimensions (H x W x D)	62 cm x 35.5 cm x 55 cm (24.4" x 14" x 21.6")	62 cm x 58 cm x 55 cm (24.4" x 22.5" x 21.6")
Weight	8.1 kg (17.8 lbs)	11.7 kg (26 lbs)
Computer Interfaces	USB and/or RS-232	USB and/or RS-232
Power Requirements	100-240 VAC, 47-63 Hz, 1.9A	100-240 VAC, 47-63 Hz, 1.9A






Technical Specifications

Minimum Computer Requirements	
Microsoft® Windows® 10	
2 GB RAM for Microsoft® Windows® 10	
Video running 1024x768 with 24-bit color	
Pentium Dual Core 2.3 GHz	
Two free communication ports, either serial and/or USB	
Internet Explorer 4 or higher must be installed for the online Help to function	

Technical Specifications	
Carrier Gas (Ar)	Variable psi not to exceed 40 psi
Power Requirements	100-240 VAC ±10%, 50/60 Hz
Height	20 cm
Width	48 cm
Depth	60 cm
Weight	37 lbs (16.8 Kg)
Computer Interfaces	RS-232 or USB
Autosampler	ASX-280, ASX-560
Warranty	12 month limited



Teledyne LABS enhances the visibility for our brands, products, and services, aiding customers in finding solutions that meet their current and future needs. The existing Teledyne brands will remain, providing ongoing value to customers.

